

IES Report

BoxRail® | 107 | White Baffle | 80 CRI | LO

107-BX-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-WB-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	52	54	54	55
Total Lumens, 4' rail length (1219mm)	763	803	803	819
Lumens per foot (305mm)	191	201	201	205
Input Power (W), 4' rail length (1219mm)	15.0	15.0	15.0	15.0
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_107_BX_LO_35_WB.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TEST] L071704206 (SOURCE REPORT FOR REFERENCE)
 [TESTLAB] REPORT BASED ON DATA PRODUCED BY NVLAP ACCREDITED LAB
 [ISSUEDATE] 11/1/2017
 [MANUFAC] Vode Lighting
 [LUMCAT] 107-BX-48-Z-LO-35-WB
 [LUMINAIRE] BoxRail LED, 48", 3500K, 80 CRI, zipper board,
 [MORE] white baffle, low output
 [TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	801
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	54
Total Luminaire Watts	14.95
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.28
Spacing Criterion (90-270)	0.76
Spacing Criterion (Diagonal)	0.98
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.08 ft
Luminous Width (90-270)	3.85 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	3321	6846	5360
55	3268	4489	4310
65	3558	3363	3510
75	1831	2069	2467
85	1182	1182	1182

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_107_BX_LO_35_WB.IES

CANDELA TABULATION

	0	5	10	15	20	25	30	35	40	45
0	619.50	619.50	619.50	619.50	619.50	619.50	619.50	619.50	619.50	619.50
5	618.32	617.73	617.14	616.55	614.78	613.01	611.24	608.88	606.52	604.16
10	611.83	611.24	608.29	604.16	597.67	591.18	584.10	577.61	570.53	564.04
15	601.21	599.44	592.95	582.92	571.71	560.50	549.88	538.67	528.05	518.02
20	584.10	580.56	569.35	554.60	539.85	523.92	508.58	493.83	477.90	461.97
25	559.91	554.60	538.08	520.38	500.32	480.26	460.20	438.37	418.31	400.02
30	531.00	523.33	502.68	480.26	455.48	430.70	404.74	379.96	355.77	334.53
35	496.78	486.75	462.56	434.83	406.51	376.42	346.92	318.01	290.28	267.27
40	296.18	298.54	307.39	319.19	322.73	309.16	282.61	253.70	224.20	197.65
45	67.26	70.21	75.52	82.60	96.76	118.59	146.32	163.43	153.99	138.65
50	59.00	61.36	64.90	69.03	73.75	80.24	87.91	94.99	99.12	102.07
55	53.69	55.46	57.23	60.18	63.72	67.85	71.98	73.16	73.16	73.75
60	50.74	51.33	51.33	51.92	52.51	54.28	54.87	55.46	56.05	56.05
65	43.07	42.48	41.89	40.71	39.53	39.53	39.53	39.53	40.12	40.71
70	27.73	27.73	27.14	25.96	25.37	25.37	25.37	25.96	26.55	27.14
75	13.57	13.57	13.57	13.57	13.57	13.57	14.16	14.75	14.75	15.34
80	7.08	7.08	7.08	6.49	6.49	6.49	6.49	6.49	7.08	7.08
85	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles **Horizontal Angles**

	50	55	60	65	70	75	80	85	90
0	619.50	619.50	619.50	619.50	619.50	619.50	619.50	619.50	619.50
5	603.57	600.03	597.67	595.90	594.13	592.95	592.36	591.77	591.77
10	560.50	554.01	548.11	543.98	541.03	538.08	536.31	535.13	534.54
15	509.76	499.73	490.29	482.62	476.72	471.41	467.87	465.51	464.92
20	447.22	436.60	421.26	411.23	402.97	396.48	391.76	389.40	388.22
25	382.32	366.39	351.05	338.66	328.04	319.78	313.88	310.34	309.16
30	315.06	295.00	278.48	264.32	252.52	243.67	237.18	233.05	231.87
35	243.67	220.66	204.73	189.39	177.59	169.92	164.61	162.25	161.07
40	173.46	156.94	148.68	143.37	139.24	136.29	133.93	132.75	132.16
45	130.98	125.08	120.95	117.41	113.87	111.51	109.74	109.15	108.56
50	101.48	99.12	96.76	94.40	92.63	90.86	89.68	88.50	88.50
55	74.93	75.52	75.52	74.34	73.16	72.57	71.98	71.39	70.80
60	56.64	56.64	57.23	57.23	57.23	57.23	56.64	56.64	56.05
65	41.30	41.30	41.89	42.48	42.48	43.07	43.07	42.48	42.48
70	27.73	28.32	28.91	29.50	29.50	30.09	30.09	30.09	30.09
75	15.93	17.11	17.11	17.70	18.29	18.29	18.88	18.88	18.29
80	7.67	7.67	8.26	8.85	8.85	8.85	9.44	9.44	9.44
85	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_107_BX_LO_35_WB.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	203.57	N.A.	25.40
0-30	393.69	N.A.	49.20
0-40	573.52	N.A.	71.60
0-60	738.38	N.A.	92.20
0-80	797.04	N.A.	99.50
0-90	800.73	N.A.	100.00
10-90	744.12	N.A.	92.90
20-40	369.95	N.A.	46.20
20-50	472.11	N.A.	59.00
40-70	205.84	N.A.	25.70
60-80	58.66	N.A.	7.30
70-80	17.68	N.A.	2.20
80-90	3.69	N.A.	0.50
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	800.73	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	56.61
10-20	146.96
20-30	190.12
30-40	179.83
40-50	102.16
50-60	62.70
60-70	40.97
70-80	17.68
80-90	3.69
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_107_BX_LO_35_WB.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80
3	97	89	83	78	95	88	82	77	85	80	76	82	78	75	80	76	73	71
4	91	81	74	69	89	80	74	69	78	72	68	76	71	67	74	70	66	64
5	85	75	67	62	83	74	67	62	72	66	61	70	65	61	68	64	60	58
6	80	69	62	56	78	68	61	56	66	60	56	65	59	55	63	59	55	53
7	75	64	56	51	73	63	56	51	62	55	51	60	55	51	59	54	50	49
8	71	59	52	47	69	59	52	47	57	51	47	56	51	47	55	50	46	45
9	67	55	48	44	65	55	48	43	54	48	43	53	47	43	52	47	43	41
10	63	52	45	40	62	51	45	40	50	44	40	49	44	40	49	44	40	38

POLAR GRAPH



Maximum Candela = 619.5 Located At Horizontal Angle = 0, Vertical Angle = 0
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)