

IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	92	94	96	98
Total Lumens, 4' rail length (1219mm)	2806	2894	2953	3012
Lumens per foot (305mm)	701	724	738	753
Lumens per foot UP (305mm)	437	451	460	469
Lumens per foot DOWN (305mm)	265	273	279	284
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.





IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 80 CRI | SO
 707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	110	113	116	118
Total Lumens, 4' rail length (1219mm)	5611	5789	5907	6025
Lumens per foot (305mm)	1403	1447	1477	1506
Lumens per foot UP (305mm)	873	901	919	938
Lumens per foot DOWN (305mm)	529	546	557	568
Input Power (W), 4' rail length (1219mm)	51.3	51.3	51.3	51.3
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	100	103	105	107
Total Lumens, 4' rail length (1219mm)	10662	10998	11223	11447
Lumens per foot (305mm)	2665	2750	2806	2862
Lumens per foot UP (305mm)	1659	1712	1747	1693
Lumens per foot DOWN (305mm)	1006	1038	1059	1026
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	79	81	83	86
Total Lumens, 4' rail length (1219mm)	2419	2495	2546	2597
Lumens per foot (305mm)	605	624	636	649
Lumens per foot UP (305mm)	376	388	396	404
Lumens per foot DOWN (305mm)	228	235	240	245
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	95	98	100	104
Total Lumens, 4' rail length (1219mm)	4837	4990	5092	5194
Lumens per foot (305mm)	1209	1248	1273	1298
Lumens per foot UP (305mm)	753	777	793	808
Lumens per foot DOWN (305mm)	456	471	480	490
Input Power (W), 4' rail length (1219mm)	51.3	51.3	51.3	51.3
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 60° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U2S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	75	89	91	95
Total Lumens, 4' rail length (1219mm)	7995	9481	9675	9868
Lumens per foot (305mm)	1999	2370	2419	2467
Lumens per foot UP (305mm)	1386	1476	1506	1459
Lumens per foot DOWN (305mm)	613	895	913	884
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.