

## IES Report



### ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	89	92	94	96
Total Lumens, 4' rail length (1219mm)	2732	2818	2876	2933
Lumens per foot (305mm)	683	705	719	733
Lumens per foot UP (305mm)	422	435	444	453
Lumens per foot DOWN (305mm)	261	269	275	280
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).





**IES Report**

**ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | SO**  
 707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	107	110	112	114
Total Lumens, 4' rail length (1219mm)	5464	5636	5751	5866
Lumens per foot (305mm)	1366	1409	1438	1467
Lumens per foot UP (305mm)	844	870	888	906
Lumens per foot DOWN (305mm)	522	539	550	561
Input Power (W), 4' rail length (1219mm)	51.5	51.5	51.5	51.5
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



### ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	97	100	102	104
Total Lumens, 4' rail length (1219mm)	10381	10709	10927	11146
Lumens per foot (305mm)	2595	2677	2732	2786
Lumens per foot UP (305mm)	1603	1654	1687	1635
Lumens per foot DOWN (305mm)	992	1024	1045	1012
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



### ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	77	79	81	84
Total Lumens, 4' rail length (1219mm)	2355	2429	2479	2529
Lumens per foot (305mm)	589	607	620	632
Lumens per foot UP (305mm)	364	375	383	390
Lumens per foot DOWN (305mm)	225	232	237	242
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	92	95	97	101
Total Lumens, 4' rail length (1219mm)	4710	4859	4958	5057
Lumens per foot (305mm)	1178	1215	1239	1264
Lumens per foot UP (305mm)	727	750	766	781
Lumens per foot DOWN (305mm)	450	464	474	483
Input Power (W), 4' rail length (1219mm)	51.5	51.5	51.5	51.5
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	84	87	88	92
Total Lumens, 4' rail length (1219mm)	8949	9232	9420	9609
Lumens per foot (305mm)	2237	2308	2355	2402
Lumens per foot UP (305mm)	1382	1425	1455	1409
Lumens per foot DOWN (305mm)	855	882	900	873
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).