

## IES Report



ZipThree® | 707 | Symmetric, up | 85° Asymmetric , down | 80 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-35-U1A1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	89	92	94	96
Total Lumens, 4' rail length (1219mm)	2734	2821	2878	2936
Lumens per foot (305mm)	684	705	720	734
Lumens per foot UP (305mm)	444	458	467	476
Lumens per foot DOWN (305mm)	240	247	253	258
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | 707 | Symmetric, up | 85° Asymmetric , down | 80 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-35-U1A1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	105	108	110	113
Total Lumens, 4' rail length (1219mm)	5468	5641	5756	5871
Lumens per foot (305mm)	1367	1410	1439	1468
Lumens per foot UP (305mm)	887	915	934	953
Lumens per foot DOWN (305mm)	480	495	505	515
Input Power (W), 4' rail length (1219mm)	52.4	52.4	52.4	52.4
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | 707 | Symmetric, up | 85° Asymmetric , down | 80 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-35-U1A1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	97	100	103	105
Total Lumens, 4' rail length (1219mm)	10390	10718	10937	11155
Lumens per foot (305mm)	2597	2679	2734	2789
Lumens per foot UP (305mm)	1686	1739	1775	1720
Lumens per foot DOWN (305mm)	912	940	960	930
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | 707 | Symmetric, up | 85° Asymmetric , down | 90 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-359-U1A1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	77	79	84	85
Total Lumens, 4' rail length (1219mm)	2357	2431	2531	2548
Lumens per foot (305mm)	589	608	633	637
Lumens per foot UP (305mm)	382	395	411	401
Lumens per foot DOWN (305mm)	207	213	222	236
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | 707 | Symmetric, up | 85° Asymmetric , down | 90 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-359-U1A1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	91	93	95	99
Total Lumens, 4' rail length (1219mm)	4714	4863	4962	5061
Lumens per foot (305mm)	1179	1216	1241	1265
Lumens per foot UP (305mm)	765	789	805	821
Lumens per foot DOWN (305mm)	414	427	435	444
Input Power (W), 4' rail length (1219mm)	52.3	52.3	52.3	52.3
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report

ZipThree® | 707 | Symmetric, up | 85° Asymmetric , down | 90 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-359-U1A1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	84	87	88	92
Total Lumens, 4' rail length (1219mm)	8957	9240	9428	9617
Lumens per foot (305mm)	2239	2310	2357	2404
Lumens per foot UP (305mm)	1453	1499	1530	1482
Lumens per foot DOWN (305mm)	786	811	827	802
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).