

IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	101	104	106	108
Total Lumens, 4' rail length (1219mm)	3093	3190	3255	3320
Lumens per foot (305mm)	773	798	814	830
Lumens per foot UP (305mm)	441	455	464	473
Lumens per foot DOWN (305mm)	332	343	350	357
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	121	125	128	130
Total Lumens, 4' rail length (1219mm)	6185	6380	6511	6641
Lumens per foot (305mm)	1546	1595	1628	1660
Lumens per foot UP (305mm)	882	910	928	947
Lumens per foot DOWN (305mm)	664	685	699	713
Input Power (W), 4' rail length (1219mm)	51.3	51.3	51.3	51.3
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	110	114	116	118
Total Lumens, 4' rail length (1219mm)	11752	12123	12370	12618
Lumens per foot (305mm)	2938	3031	3093	3154
Lumens per foot UP (305mm)	1676	1728	1764	1709
Lumens per foot DOWN (305mm)	1262	1302	1329	1288
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	87	90	92	96
Total Lumens, 4' rail length (1219mm)	2666	2750	2806	2862
Lumens per foot (305mm)	667	688	702	716
Lumens per foot UP (305mm)	380	392	400	408
Lumens per foot DOWN (305mm)	286	295	301	307
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	105	108	110	114
Total Lumens, 4' rail length (1219mm)	5332	5500	5613	5725
Lumens per foot (305mm)	1333	1375	1403	1431
Lumens per foot UP (305mm)	760	784	800	816
Lumens per foot DOWN (305mm)	573	591	603	615
Input Power (W), 4' rail length (1219mm)	51.3	51.3	51.3	51.3
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	95	98	100	104
Total Lumens, 4' rail length (1219mm)	10131	10451	10664	10877
Lumens per foot (305mm)	2533	2613	2666	2719
Lumens per foot UP (305mm)	1444	1490	1520	1473
Lumens per foot DOWN (305mm)	1088	1123	1146	1110
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.