

## IES Report



# RaceRail® | 107 | 120° FlyWing™ | 80 CRI | LO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	108	111	114	114
Total Lumens, 4' rail length (1219mm)	1482	1528	1560	1560
Lumens per foot (305mm)	370	382	390	390
Input Power (W), 4' rail length (1219mm)	13.8	13.8	13.8	13.8
Watts per foot (305mm)	3.5	3.5	3.5	3.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# RaceRail® | 107 | 120° FlyWing™ | 80 CRI | SO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-35-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	124	128	131	131
Total Lumens, 4' rail length (1219mm)	2963	3057	3119	3119
Lumens per foot (305mm)	741	764	780	780
Input Power (W), 4' rail length (1219mm)	23.9	23.9	23.9	23.9
Watts per foot (305mm)	6.0	6.0	6.0	6.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# RaceRail® | 107 | 120° FlyWing™ | 80 CRI | HO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-35-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	115	119	121	121
Total Lumens, 4' rail length (1219mm)	5630	5808	5927	5927
Lumens per foot (305mm)	1408	1452	1482	1482
Input Power (W), 4' rail length (1219mm)	49.1	49.1	49.1	49.1
Watts per foot (305mm)	12.3	12.3	12.3	12.3
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# RaceRail® | 107 | 120° FlyWing™ | 90 CRI | LO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-359-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	93	96	98	99
Total Lumens, 4' rail length (1219mm)	1277	1318	1345	1358
Lumens per foot (305mm)	319	329	336	339
Input Power (W), 4' rail length (1219mm)	13.8	13.8	13.8	13.8
Watts per foot (305mm)	3.5	3.5	3.5	3.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# RaceRail® | 107 | 120° FlyWing™ | 90 CRI | SO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-359-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	107	110	113	114
Total Lumens, 4' rail length (1219mm)	2555	2635	2689	2716
Lumens per foot (305mm)	639	659	672	679
Input Power (W), 4' rail length (1219mm)	24.0	24.0	24.0	24.0
Watts per foot (305mm)	6.0	6.0	6.0	6.0
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report

# RaceRail® | 107 | 120° FlyWing™ | 90 CRI | HO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-359-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	99	103	105	106
Total Lumens, 4' rail length (1219mm)	4854	5007	5109	5160
Lumens per foot (305mm)	1213	1252	1277	1290
Input Power (W), 4' rail length (1219mm)	49.1	49.1	49.1	49.1
Watts per foot (305mm)	12.3	12.3	12.3	12.3
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).