



## IES Report



### ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	114	117	120	120
Total Lumens, 4' rail length (1219mm)	3375	3481	3552	3552
Lumens per foot (305mm)	494	509	520	520
Lumens per foot UP (305mm)	350	361	368	368
Lumens per foot DOWN (305mm)	844	870	888	888
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	130	134	136	136
Total Lumens, 4' rail length (1219mm)	6749	6963	7105	7105
Lumens per foot (305mm)	988	1019	1040	1040
Lumens per foot UP (305mm)	700	722	736	736
Lumens per foot DOWN (305mm)	1687	1741	1776	1776
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



### ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	120	123	126	126
Total Lumens, 4' rail length (1219mm)	12824	13229	13499	13499
Lumens per foot (305mm)	1877	1936	1975	1975
Lumens per foot UP (305mm)	1329	1371	1399	1399
Lumens per foot DOWN (305mm)	3206	3307	3375	3375
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



### ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	98	101	103	107
Total Lumens, 4' rail length (1219mm)	2909	3001	3062	3093
Lumens per foot (305mm)	426	439	448	453
Lumens per foot UP (305mm)	302	311	317	321
Lumens per foot DOWN (305mm)	727	750	766	773
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI*	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



### ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	113	116	119	124
Total Lumens, 4' rail length (1219mm)	5818	6002	6125	6186
Lumens per foot (305mm)	851	878	896	905
Lumens per foot UP (305mm)	603	622	635	641
Lumens per foot DOWN (305mm)	1455	1501	1531	1546
Input Power (W), 4' rail length (1219mm)	51.8	51.8	51.8	51.8
Watts per foot (305mm)	13	13	13	13
CRI*	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report

### ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U2S7-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	103	106	109	113
Total Lumens, 4' rail length (1219mm)	11055	11404	11637	11753
Lumens per foot (305mm)	1618	1669	1703	1720
Lumens per foot UP (305mm)	1146	1182	1206	1218
Lumens per foot DOWN (305mm)	2764	2851	2909	2938
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27	27	27	27
CRI*	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).