

IES Report



ZipTwo® | 707 | Square, Diffuse | 80 CRI | LO

707-Z2-4-48-XX-XX-X-0-Z-LO-35-S6-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	127	131	134	134
Total Lumens, 4' rail length (1219mm)	1886	1945	1985	1985
Lumens per foot (305mm)	471	486	496	496
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square, Diffuse | 80 CRI | SO

707-Z2-4-48-XX-XX-X-0-Z-SO-35-S6-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	145	150	153	153
Total Lumens, 4' rail length (1219mm)	3771	3891	3970	3970
Lumens per foot (305mm)	943	973	992	992
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square, Diffuse | 80 CRI | HO

707-Z2-4-48-XX-XX-X-0-Z-HO-35-S6-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	144	148	151	151
Total Lumens, 4' rail length (1219mm)	5657	5836	5955	5955
Lumens per foot (305mm)	1414	1459	1489	1489
Input Power (W), 4' rail length (1219mm)	39.6	39.6	39.6	39.6
Watts per foot (305mm)	9.9	9.9	9.9	9.9
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square, Diffuse | 90 CRI | LO

707-Z2-4-48-XX-XX-X-0-Z-LO-359-S6-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	110	113	115	117
Total Lumens, 4' rail length (1219mm)	1626	1677	1711	1728
Lumens per foot (305mm)	406	419	428	432
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipTwo® | 707 | Square, Diffuse | 90 CRI | SO

707-Z2-4-48-XX-XX-X-0-Z-SO-359-S6-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	125	129	132	133
Total Lumens, 4' rail length (1219mm)	3251	3354	3422	3457
Lumens per foot (305mm)	813	838	856	864
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

ZipTwo® | 707 | Square, Diffuse | 90 CRI | HO

707-Z2-4-48-XX-XX-X-0-Z-HO-359-S6-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	124	128	130	132
Total Lumens, 4' rail length (1219mm)	4877	5031	5134	5185
Lumens per foot (305mm)	1219	1258	1283	1296
Input Power (W), 4' rail length (1219mm)	39.6	39.6	39.6	39.6
Watts per foot (305mm)	9.9	9.9	9.9	9.9
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).