

IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | Soft Diffuse, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U1D2-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	107	110	112	112
Total Lumens, 4' rail length (1219mm)	3165	3265	3332	3332
Lumens per foot (305mm)	791	816	833	833
Lumens per foot UP (305mm)	441	455	464	464
Lumens per foot DOWN (305mm)	351	362	369	369
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | Soft Diffuse, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U1D2-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	122	126	128	128
Total Lumens, 4' rail length (1219mm)	6331	6531	6664	6664
Lumens per foot (305mm)	1583	1633	1666	1666
Lumens per foot UP (305mm)	882	909	928	928
Lumens per foot DOWN (305mm)	701	723	738	738
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | Soft Diffuse, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U1D2-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	112	116	118	118
Total Lumens, 4' rail length (1219mm)	12029	12409	12662	12662
Lumens per foot (305mm)	3007	3102	3165	3165
Lumens per foot UP (305mm)	1675	1728	1763	1763
Lumens per foot DOWN (305mm)	1332	1374	1402	1402
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | Soft Diffuse, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U1D2-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	92	95	97	98
Total Lumens, 4' rail length (1219mm)	2729	2815	2873	2901
Lumens per foot (305mm)	682	704	718	725
Lumens per foot UP (305mm)	380	392	400	404
Lumens per foot DOWN (305mm)	302	312	318	321
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | Soft Diffuse, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U1D2-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	105	108	111	112
Total Lumens, 4' rail length (1219mm)	5458	5630	5745	5802
Lumens per foot (305mm)	1364	1408	1436	1451
Lumens per foot UP (305mm)	760	784	800	808
Lumens per foot DOWN (305mm)	605	624	636	643
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric, up | Soft Diffuse, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U1D2-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	97	100	102	103
Total Lumens, 4' rail length (1219mm)	10370	10697	10916	11025
Lumens per foot (305mm)	2592	2674	2729	2756
Lumens per foot UP (305mm)	1444	1489	1520	1535
Lumens per foot DOWN (305mm)	1149	1185	1209	1221
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.