

IES Report

ZipTwo® | 707 | 60° Symmetric | 80 CRI | HO

707-Z2-4-48-XX-XX-X-0-Z-HO-35-S2-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	91	93	95	95
Total Lumens, 4' rail length (1219mm)	3562	3674	3749	3749
Lumens per foot (305mm)	890	919	937	937
Input Power (W), 4' rail length (1219mm)	39.6	39.6	39.6	39.6
Watts per foot (305mm)	9.9	9.9	9.9	9.9
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES INDOOR REPORT

PHOTOMETRIC FILENAME : VODE_707_Z2_HO_359_S2.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] L121911524 (SOURCE REPORT FOR REFERENCE

[TESTLAB] REPORT BASED ON DATA FROM NVLAP ACCREDITED LAB

[ISSUE DATE] 12/23/2019

[MANUFAC] Vode Lighting

[LUMCAT] 707-Z2-48-Z-HO-35-S2-AL

[LUMINAIRE] ZipTwo LED, 48", 3500K, 80 CRI, zipper board, 60° white symmetric lens,

[MORE] high output, clear anodized finish

[TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	3749
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	95
Total Luminaire Watts	39.55
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.94
Spacing Criterion (90-270)	1.14
Spacing Criterion (Diagonal)	1.04
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.02 ft
Luminous Width (90-270)	3.98 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	72472	126826	193647
55	44262	73770	133196
65	34486	51729	96783
75	29972	39963	69935
85	26971	32366	43154

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_707_Z2_HO_359_S2.IES

CANDELA TABULATION

	<u>0</u>	<u>5</u>	<u>10</u>	<u>15</u>	<u>20</u>	<u>25</u>	<u>30</u>	<u>35</u>	<u>40</u>	<u>45</u>
0.0	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66
1.0	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66
3.0	2535.18	2535.18	2535.18	2535.18	2535.18	2535.18	2535.18	2535.18	2535.18	2535.18
5.0	2524.74	2524.74	2524.74	2524.74	2524.74	2526.48	2526.48	2526.48	2526.48	2526.48
7.0	2509.08	2509.08	2509.08	2509.08	2510.82	2510.82	2510.82	2514.30	2514.30	2512.56
9.0	2481.24	2481.24	2482.98	2482.98	2484.72	2486.46	2488.20	2489.94	2491.68	2493.42
11.0	2442.96	2442.96	2444.70	2446.44	2449.92	2453.40	2456.88	2460.36	2463.84	2465.58
13.0	2390.76	2390.76	2392.50	2395.98	2401.20	2406.42	2413.38	2418.60	2425.56	2430.78
15.0	2321.16	2321.16	2324.64	2331.60	2338.56	2347.26	2357.70	2368.14	2376.84	2385.54
17.0	2232.42	2235.90	2241.12	2249.82	2260.26	2274.18	2288.10	2303.76	2317.68	2331.60
19.5	2091.48	2094.96	2103.66	2115.84	2134.98	2154.12	2176.74	2201.10	2223.72	2244.60
22.5	1882.68	1886.16	1900.08	1919.22	1945.32	1976.64	2011.44	2046.24	2081.04	2114.10
25.5	1637.34	1642.56	1658.22	1684.32	1719.12	1760.88	1807.86	1856.58	1907.04	1954.02
29.0	1331.10	1336.32	1355.46	1386.78	1428.54	1479.00	1538.16	1600.80	1666.92	1729.56
33.0	997.02	1003.98	1023.12	1054.44	1096.20	1153.62	1216.26	1287.60	1364.16	1440.72
37.5	689.04	694.26	711.66	737.76	776.04	826.50	883.92	955.26	1033.56	1111.86
42.5	452.40	455.88	468.06	487.20	515.04	553.32	598.56	654.24	718.62	786.48
47.5	306.24	307.98	316.68	328.86	348.00	374.10	405.42	443.70	488.94	541.14
55.0	187.92	187.92	193.14	200.10	210.54	222.72	240.12	259.26	285.36	313.20
65.0	107.88	109.62	111.36	113.10	118.32	123.54	130.50	139.20	149.64	161.82
75.0	57.42	57.42	57.42	59.16	60.90	62.64	64.38	67.86	71.34	76.56
85.0	17.40	17.40	17.40	17.40	19.14	19.14	19.14	19.14	19.14	20.88
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles **Horizontal Angles**

	<u>50</u>	<u>55</u>	<u>60</u>	<u>65</u>	<u>70</u>	<u>75</u>	<u>80</u>	<u>85</u>	<u>90</u>
0.0	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66
1.0	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66	2538.66
3.0	2535.18	2535.18	2535.18	2535.18	2535.18	2535.18	2535.18	2535.18	2535.18
5.0	2528.22	2528.22	2528.22	2528.22	2528.22	2528.22	2528.22	2528.22	2529.96
7.0	2516.04	2516.04	2516.04	2517.78	2517.78	2517.78	2517.78	2517.78	2517.78
9.0	2495.16	2496.90	2498.64	2498.64	2500.38	2500.38	2500.38	2502.12	2500.38
11.0	2469.06	2472.54	2474.28	2476.02	2476.02	2477.76	2477.76	2479.50	2479.50
13.0	2436.00	2439.48	2442.96	2446.44	2448.18	2448.18	2449.92	2449.92	2449.92
15.0	2394.24	2401.20	2404.68	2409.90	2411.64	2413.38	2413.38	2415.12	2415.12
17.0	2343.78	2352.48	2361.18	2366.40	2369.88	2371.62	2371.62	2373.36	2373.36
19.5	2262.00	2277.66	2289.84	2296.80	2302.02	2305.50	2307.24	2305.50	2305.50
22.5	2143.68	2166.30	2185.44	2197.62	2206.32	2209.80	2211.54	2211.54	2211.54
25.5	1995.78	2030.58	2056.68	2075.82	2088.00	2093.22	2094.96	2094.96	2094.96
29.0	1788.72	1837.44	1875.72	1903.56	1919.22	1927.92	1931.40	1933.14	1933.14
33.0	1517.28	1579.92	1633.86	1670.40	1694.76	1708.68	1713.90	1715.64	1715.64
37.5	1193.64	1268.46	1331.10	1379.82	1412.88	1433.76	1444.20	1447.68	1447.68
42.5	859.56	932.64	998.76	1052.70	1094.46	1120.56	1137.96	1146.66	1148.40
47.5	598.56	657.72	715.14	765.60	809.10	840.42	863.04	875.22	878.70
55.0	346.26	382.80	421.08	459.36	494.16	525.48	548.10	562.02	565.50
65.0	175.74	193.14	212.28	231.42	252.30	271.44	287.10	297.54	302.76
75.0	81.78	88.74	95.70	104.40	113.10	120.06	127.02	132.24	133.98
85.0	20.88	22.62	22.62	24.36	24.36	26.10	26.10	27.84	27.84
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_707_Z2_HO_359_S2.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	864.73	N.A.	23.10
0-30	1700.97	N.A.	45.40
0-40	2404.67	N.A.	64.10
0-60	3297.54	N.A.	87.90
0-80	3685.94	N.A.	98.30
0-90	3749.42	N.A.	100.00
10-90	3554.67	N.A.	94.80
20-40	1539.93	N.A.	41.10
20-50	2139.02	N.A.	57.00
40-70	1143.48	N.A.	30.50
60-80	388.40	N.A.	10.40
70-80	137.79	N.A.	3.70
80-90	63.48	N.A.	1.70
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	3749.42	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	194.75
10-20	669.98
20-30	836.24
30-40	703.69
40-50	599.09
50-60	293.79
60-70	250.61
70-80	137.79
80-90	63.48
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_707_Z2_HO_359_S2.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	107	103	100	108	104	101	98	100	98	95	96	94	92	93	91	90	88
2	103	96	90	85	100	94	89	84	91	86	82	87	84	81	84	81	79	77
3	95	86	80	74	93	85	79	74	82	77	72	80	75	71	77	73	70	68
4	89	79	71	65	87	77	70	65	75	69	64	73	68	63	71	66	63	61
5	83	72	64	58	81	71	63	58	69	62	58	67	61	57	65	60	56	55
6	77	66	58	53	76	65	58	52	63	57	52	62	56	52	60	55	51	49
7	73	61	53	48	71	60	53	48	59	52	47	57	51	47	56	51	47	45
8	68	56	49	44	67	56	48	44	54	48	43	53	47	43	52	47	43	41
9	64	52	45	40	63	52	45	40	51	44	40	50	44	40	49	43	39	38
10	61	49	42	37	59	48	42	37	47	41	37	47	41	37	46	40	37	35

POLAR GRAPH



Maximum Candela = 2538.66 Located At Horizontal Angle = 0, Vertical Angle = 0
1 - Vertical Plane Through Horizontal Angles (0 - 180)
2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)