

IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	91	94	96	96
Total Lumens, 4' rail length (1219mm)	2702	2787	2844	2844
Lumens per foot (305mm)	675	697	711	711
Lumens per foot UP (305mm)	465	480	490	490
Lumens per foot DOWN (305mm)	210	217	221	221
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	104	107	109	109
Total Lumens, 4' rail length (1219mm)	5403	5574	5688	5688
Lumens per foot (305mm)	1351	1393	1422	1422
Lumens per foot UP (305mm)	931	960	980	980
Lumens per foot DOWN (305mm)	420	433	442	442
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	96	99	101	101
Total Lumens, 4' rail length (1219mm)	10266	10590	10807	10807
Lumens per foot (305mm)	2567	2648	2702	2702
Lumens per foot UP (305mm)	1768	1824	1861	1861
Lumens per foot DOWN (305mm)	798	823	840	840
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	79	81	83	84
Total Lumens, 4' rail length (1219mm)	2329	2403	2452	2476
Lumens per foot (305mm)	582	601	613	619
Lumens per foot UP (305mm)	401	414	422	426
Lumens per foot DOWN (305mm)	181	187	191	193
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	90	92	95	95
Total Lumens, 4' rail length (1219mm)	4658	4805	4903	4952
Lumens per foot (305mm)	1165	1201	1226	1238
Lumens per foot UP (305mm)	802	828	845	853
Lumens per foot DOWN (305mm)	362	374	381	385
Input Power (W), 4' rail length (1219mm)	52.2	52.2	51.8	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	83	85	87	88
Total Lumens, 4' rail length (1219mm)	8850	9130	9316	9409
Lumens per foot (305mm)	2213	2282	2329	2352
Lumens per foot UP (305mm)	1524	1573	1605	1621
Lumens per foot DOWN (305mm)	688	710	724	732
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27	27	27	27
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.